

General Product Specifications

DPP-255 Printers

Printing Method	Direct line thermal printer
Printing Speed	Max 100 mm per second Max 62 mm per second (Peeling)
Printing Width	48 mm (384 dots)
Resolution	203dpi (8x9 dots/mm)
Resident Fonts	Font A: 48 characters per line Font B: 64 characters per line
Loadable Fonts	Font C: 48 characters per line Font D: 64 characters per line
Logo Registration	1 Black and White (384 x 248 dots)
Input Buffer	30k bytes
Communications	RS-232C port (max 115200bps) mini USB 2.0 port (device) Bluetooth 2.0 class 2 (Serial Port Profile) Bluetooth 3.0 class 2 (Serial Port Profile, iPod Accessory Protocol) Wireless LAN 802.11b (Optional)
Emulation	ESC/POS Eltron ZPL
Compatibility	Android, iOS (Mfi certified), Windows, BlackBerry
Reliability	50km (Thermal head) 15 000 000 lines (Mechanism MCBF)
Paper Width	25.4 to 58 mm
Paper Thickness	Receipt: 60 to 150 µm Label: Max. 165 µm
Paper Features	Easy paper loading Black Mark Label Gap Peeled label
Post Printing Features	Peeler
Resident Barcodes	1D: EAN 13, EAN 8, UPC A, UPC E, Code 39, Code 93, Code 128, Codabar, 2 of 5 interleaved 2D: PDF417, QR code
Operating Temperature	+10°C to +50°C @ 35 to 85% RH
Storage Temperature	-20°C to +60°C @ 10 to 90% RH
Dimensions	88mm x 120mm x 64mm
Weight	420 g
Battery	Rechargeable Li-Ion battery 7.4V, 2000mAh 2.5 hours charging time 20 000 lines per fully charged battery



www.stimare.net

www.lineapro.store

info@stimare.net

info@lineapro.store

USA +1-720-257-7070

UK +44-208-0998071

Ireland +353-1-6854600

We are the experts in:

BARCODE SCANNING

MOBILE PRINTING

POINT-OF-SALE (POS)