

General Product Specifications

DPP-350 Printers



Printing Method	Line thermal dot printing
Printing Speed	Max 60 mm per second
Printing Width	72 mm (576 dots)
Resolution	203dpi (8x9 dots/mm)
Dot Density	Horizontal – 0.125 mm (8 dots/mm) Vertical – 0.125 mm (8 dots/mm)
Resident Fonts	Font A: 12 x 24 dots (48 char. per line) Font B: 9 x 16 dots (64 char. per line)
Loadable Fonts	Font C: 12 x 24 dots (48 char. per line) Font D: 9 x 16 dots (64 char. per line)
Logo Registration	1 Black and White (576 x 248 dots)
Input Buffer	36,864 bytes
Communications	RS232 C – max. 115200 bps. USB v 1.1, compatible with 2.0 Bluetooth
Emulation	ESC/POS Continuous paper mode
Compatibility	Android, iOS (Mfi certified), Windows, Blackberry
Reliability	Printing Head: 50km (printing rate 25% max)
Paper Width	78 and 58 mm
Paper Thickness	60 to 65 µm
Resident Barcodes	1D – EAN13, EAN8, UPC-A, UPC-E, Codebar, Code39, Code128 2D – PDF417, QR Code
Magnetic Card Reader (optional)	3-track bidirectional reading, ISO 7810, ISO 7811, ISO 7813
Smart Card Reader (optional)	ISO 7816
Contactless Card Reader (optional)	MiFARE Mini MiFARE Classic 1K / 4K MiFARE Ultra-Light / Ultra-Light-C MiFARE Plus 2K / 4K ISO / IEC 14443 A ISO / IEC 15693 FeliCa
Operating Temperature	+10°C to +40°C @ 35 to 85% RH
Storage Temperature	-20°C to +60°C @ 10 to 90% RH
Dimensions	108 x 111 x 63 mm 108 x 120 x 63 mm (with MCR or/and SCR)
Weight	400g
Battery	Rechargeable Li-Ion battery 7.4 V, 2000 mAh 3 hours charging time 30 000 lines with one charge

www.stimare.net

www.lineapro.store

info@stimare.net

info@lineapro.store

USA +1-720-257-7070

UK +44-208-0998071

Ireland +353-1-6854600

We are the experts in:

BARCODE SCANNING

MOBILE PRINTING

POINT-OF-SALE (POS)