

General Product Specifications

DPP-450 Printers

Printing Method	Line thermal dot printing
Printing Speed	Max 150 mm per second
Printing Width	104 mm (832 dots)
Resolution	203dpi (8x9 dots/mm)
Dot Density	Horizontal – 0.125 mm (8 dots/mm) Vertical – 0.125 mm (8 dots/mm)
Resident Fonts	Font A: 12 x 24 dots (48 char. per line) Font B: 9 x 16 dots (64 char. per line)
Loadable Fonts	Font C: 12 x 24 dots (48 char. per line) Font D: 9 x 16 dots (64 char. per line)
Logo Registration	1 Black and White size: 832 x 248 dots
Input Buffer	128 KB (131072 bytes)
Communications	RS232 C – max. 115200 bps. USB v 1.1, compatible with 2.0 Bluetooth
Emulation	ESC/POS Continuous paper mode
Compatibility	Android, iOS (Mfi certified), Windows
Reliability	Printing Head: 50km (printing rate 25% max)
Paper Width	115mm
Paper Thickness	59 to 154 µm
Resident Barcodes	1D – EAN13, EAN8, UPC-A, UPC-E, Codebar, Code39, Code128 2D – PDF417, QR Code
Operating Temperature	+15°C to +50°C @ 35 to 85% RH
Storage Temperature	-20°C to +60°C @ 10 to 90% RH
Dimensions	157mm (W) x 138mm (D) x 67mm (H)
Weight	785 g
Battery	Rechargeable Li-Ion battery 7.4 V, 2200 mAh 2.5 hours charging time 20 000 lines with one charge



www.stimare.net
www.lineapro.store
info@stimare.net
info@lineapro.store

USA +1-720-257-7070
UK +44-208-0998071
Ireland +353-1-6854600

We are the experts in:
BARCODE SCANNING
MOBILE PRINTING
POINT-OF-SALE (POS)