



General Product Specifications

Infinea Omni

Input Power	PoE class 0, IEEE802.3af compliant, RJ-45, Cat5e, 36V to 57V input, 5V 2.4A max output
Compatibility	iPad Air, iPad Air 2
Barcode Scanner	2D High Speed Imager
Barcode Type	1D symbologies: EAN/UPC, GS1 Databar (limited expanded & omnidirectional), RSS, Code 39, Code 128, UCC/EAN 128, ISBN, ISBT, Interleaved/Matrix/Industrial and Standard 2 of 5, Codabar, Code 93/93i, Code 11, MSI, Plessey, Telepen. Postal codes: Australian Post, BPO, Canada Post, Dutch Post, Japan Post, PostNet, Sweden Post. 2D symbologies: Data Matrix, Reversed Data Matrix, PDF417, Micro PDF417, Codablock, Maxicode, QR, Aztec, GS1 composite codes.
LEDs	Green LED indicates that there is PoE power to the RJ-45 connector panel
Buttons	Home Button Scanner Hardware Reset Button
Battery	Rechargeable Li-ion Battery
Communications	Ethernet
Operating Environment	Operating temperature: +10°C to +40°C Operating humidity: 5 to 90% RH Storage temperature: -20°C to +50°C Storage humidity: 5 to 90% RH
Dimensions	283mm x 225mm x 84mm
Weight	1250 grams (44.1 oz) without iPad Air
Software Support	SDK for iOS platform
Certifications	UL, CE, FCC, RoHS, RCM (North America)



www.stimare.net
www.lineapro.store
info@stimare.net
info@lineapro.store

USA +1-720-257-7070
UK +44-208-0998071
Ireland +353-1-6854600

We are the experts in:
BARCODE SCANNING
MOBILE PRINTING
POINT-OF-SALE (POS)