



General Product Specifications

Infinea Tab 4 MSR

Power Supply	DC 5V through mini USB DC 5V through single or 5-station charger
Device Charging	Charging via USB connector through mini-USB cable, using a minimum of 1A USB charger (Apple's AC adapter acceptable)
Compatibility	iPad 4
Power Consumption	Deep sleep -20uA
Magnetic Stripe Reader	3-track bidirectional reading capabilities Type: ISO 7816-1/2/3 compatible & RAW mode
Barcode Scanner	No scan engine
Encryption and Key Management (optional)	DUKPT and Fixed Key Management 3DES-112, AES-128, AES-256 encryption algorithms
LEDs	2 LEDs for device status
Buttons	2 scanning buttons
Battery	Rechargeable Li-ion Battery 3,7V 1100mAh Charging from USB port or Single/Gang Charger
Cables	Standard USB A to mini B cable
Communications	USB Interface - between Infinea Tab 4 and iPad 4 USB synchronization between iPad 4 & PC
Audio Indicator	Electromagnetic Buzzer
Operating Environment	Operating temperature: 0°C to +40°C Operating humidity: 35 to 85% RH Storage temperature: -5°C to +40°C Storage humidity: 10 to 90% RH
Dimensions	128mm x 44mm x 51mm
Weight	116 grams with battery and barcode scanner (without iPad)
Software Support	SDK for iOS platform
Certifications	CE, FCC, Apple Mfi, Optional PCI Compliance (PCI PTS 3.x SRED)



www.stimare.net

www.lineapro.store

info@stimare.net

info@lineapro.store

USA +1-720-257-7070

UK +44-208-0998071

Ireland +353-1-6854600

We are the experts in:

BARCODE SCANNING

MOBILE PRINTING

POINT-OF-SALE (POS)