



General Product Specifications

Infinea Tab M MSR

Power Supply	DC 5V through mini USB DC 5V through Single or 5 stations charger
Device Charging	Charging via USB connector through mini-USB cable, using a minimum of 1A USB charger (Apple's AC adapter acceptable)
Compatibility	iPad mini, iPad mini 2, iPad mini 3, iPad mini 4, iPad Air, iPad Air 2, iPad Pro (9.7")
Power Consumption	Deep sleep -20uA
Magnetic Stripe Reader	3-track bidirectional reading capabilities Type: ISO 7816-1/2/3 compatible & RAW mode
Barcode Scanner	No scan engine
Bluetooth (optional)	Bluetooth 2.0 Class 2, Distance - up to 10m, Serial port profile (SPP)
Encryption and Key Management (optional)	3DES-112 (DUKPT) key management, AES-128 with Fixed or DUKPT key management. AES-256 with Fixed key management, Voltage Secure Data Encryption and Key Management: TEP2 Protocol
NFC	Supports major NFC contactless schemes
LEDs	Green LED for battery Blue LED for device status Four LEDs for contactless indication
Buttons	Status button
Battery	Rechargeable Li-ion Battery 3,7V 1300mAh Charging from USB port or Single/Gang Charger
Cables	Standard USB A to mini B cable
Communications	USB Interface - between Infinea Tab M and iOS device USB Synchronization between iOS device & PC External RS
Audio Indicator	Electromagnetic Buzzer
Operating Environment	Operating temperature: 0°C to +40°C Operating humidity: 35 to 85% RH Storage temperature: -5°C to +40°C Storage humidity: 10 to 90% RH
Dimensions	103mm x 88mm x 23.5mm
Weight	140g with battery and 2D barcode reader (without device)
Software Support	SDK for iOS platform
Certifications	CE, FCC, Apple Mfi, Optional PCI Compliance (PCI PTS 3.x SRED)



www.stimare.net
www.lineapro.store
info@stimare.net
info@lineapro.store

USA +1-720-257-7070
UK +44-208-0998071
Ireland +353-1-6854600

We are the experts in:
BARCODE SCANNING
MOBILE PRINTING
POINT-OF-SALE (POS)