

General Product Specifications

Linea Pro 5 MSR

Power Supply	Internal voltage 3.3V & 5V
Compatibility	iPhone 5/5s, iPhone SE, iPod Touch 5 and 6
Power Consumption	Deep sleep -20uA
Magnetic Stripe Reader	3-track bidirectional reading capabilities Type: ISO 7816-1/2/3 compatible & RAW mode
Barcode Scanner	No barcode scanner
Encryption and Key (optional)	Encryption capable MSR. 3DES-112, AES 128/256, DUKPT
LEDs	4 LEDs for battery status
Buttons	Battery status button
Battery	Rechargeable Li-ion Battery 3, 7V 1300mAh (USB or station charger)
Cables	Standard USB A to mini B cable
Audio Indicator	Electromagnetic Buzzer
Operating Environment	Operating temperature: 0°C to +40°C Operating humidity: 35 to 85% RH Storage temperature: -5°C to +40°C Storage humidity: 10 to 90% RH
Dimensions	1D scanner 142mm x 69mm x 22mm 2D scanner 142mm x 69mm x 27mm
Weight	120 grams
Software Support	SDK for iOS platform
Certifications	CE, FCC, Apple Mfi, Optional PCI Compliance (PCI PTS 3.x SRED)



www.stimare.net

www.lineapro.store

info@stimare.net

info@lineapro.store

USA +1-720-257-7070

UK +44-208-0998071

Ireland +353-1-6854600

We are the experts in:

BARCODE SCANNING

MOBILE PRINTING

POINT-OF-SALE (POS)