

## General Product Specifications

# Linea Pro 5 Scanners

<b>Power Supply</b>	Internal voltage 3.3V & 5V
<b>Compatibility</b>	iPhone 5/5s, iPhone SE, iPod Touch 5th, 6th and 7th Gen
<b>Power Consumption</b>	Deep sleep -20uA
<b>Magnetic Stripe Reader</b>	3-track bidirectional reading capabilities Type: ISO 7816-1/2/3 compatible & RAW mode
<b>Barcode Scanner</b>	1D Opticon MDL-1000 Laser 2D Newland EM3070 - Image Sensor 752x480 CMOS (optional) 2D Intermec EA30 - Image Sensor 752x480 CMOS (optional)
<b>Bluetooth (optional)</b>	Bluetooth 1.1 Class 2, Distance - Up to 10m, Serial port profile (SPP)
<b>Barcode Type</b>	1D symbologies: JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128(EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey. Postal code: Chinese Post, Korean Postal Authority code. Composite codes, MicroPDF417, PDF417 1D and 2D symbologies: Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey, PDF417, Data Matrix (ECC200, ECC000, 050, 080, 100, 140), QR Code
<b>Encryption and Key (optional)</b>	Encryption capable MSR. 3DES-112, AES 128/256, DUKPT
<b>RFID Reader (optional)</b>	MIFARE MINI MIFARE CLASSIC-1K, MIFARE CLASSIC-4K MIFARE ULTRALIGHT, ULTRALIGHT-C ISO 14443, ISO 15693 MIFARE PLUS 2K/4K DESFire card
<b>LEDs</b>	4 LEDs for battery status
<b>Buttons</b>	Scanning button Battery status button
<b>Battery</b>	Rechargeable Li-ion Battery 3, 7V 1300mAh (USB or station charger)
<b>Cables</b>	Standard USB A to mini B cable
<b>Audio Indicator</b>	Electromagnetic Buzzer
<b>Operating Environment</b>	Operating temperature: 0°C to +40°C Operating humidity: 35 to 85% RH Storage temperature: -5°C to +40°C Storage humidity: 10 to 90% RH
<b>Dimensions</b>	1D scanner 142mm x 69mm x 22mm 2D scanner 142mm x 69mm x 27mm
<b>Weight</b>	120 grams
<b>Software Support</b>	SDK for iOS platform
<b>Certifications</b>	CE, FCC, Apple Mfi, Optional PCI Compliance (PCI PTS 3.x SRED)



[www.stimare.net](http://www.stimare.net)

[www.lineapro.store](http://www.lineapro.store)

[info@stimare.net](mailto:info@stimare.net)

[info@lineapro.store](mailto:info@lineapro.store)

**USA** +1-720-257-7070

**UK** +44-208-0998071

**Ireland** +353-1-6854600

We are the experts in:

**BARCODE SCANNING**

**MOBILE PRINTING**

**POINT-OF-SALE (POS)**