



General Product Specifications

Infinea X7 Scanners

Device Charging	5V through Heel Cup Charger or Station charger (sold separately)
Compatibility	iPhone 7, iPhone 8 (also compatible with iPhone 6/6S*)
Power Consumption	Deep sleep -20uA
Barcode Scanner	Zebra SE4730 2D
Bluetooth	Bluetooth 3.0 Class 2 Distance - Up to 10m Serial Port Profile (SPP)
Barcode Type	Supports all major 1D or 2D barcodes, including 1D symbologies: EAN/UPC, GS1 Databar (limited expanded & omni-directional), RSS, Code 39, Code 128,UCC/EAN 128, ISBN, ISBT, Interleaved/ Matrix/Industrial and Standard 2 of 5, Codabar, Code 93/93i, Code 11, MSI, Plessey, Telepen. Postal codes 2D symbologies: Data Matrix, Reversed Data Matrix, PDF417, Micro PDF417, Codablock, Maxicode, QR, Aztec, GS1 composite codes.
RFID Reader	MIFARE MINI MIFARE CLASSIC-1K, MIFARE CLASSIC-4K MIFARE ULTRALIGHT, ULTRALIGHT-C ISO 14443, ISO 15693 MIFARE PLUS 2K/4K DESFire card FeliCa
Protection Features	IP54+ dust/fluid protection Built-in antimicrobial materials Protective tempered glass Sanitation compatible
Drop Rating	1.22 metres (4 feet)
LEDs	4 programmable color LEDs (green, blue, red and orange)
Buttons	Scan button Battery status button Speaker front/rear toggle button
Battery	User-replaceable rechargeable hard pack Li-polymer Battery 3.7V 1900mAh (Standard) or extended 3800mAH (optional)
Cables	Standard USB A to mini B cable
Audio Indicator	Electromagnetic buzzer and loud speaker
Operating Environment	Operating temperature: -10°C to +40°C Operating humidity: 5 to 90% RH Storage temperature: -20°C to +50°C Storage humidity: 5 to 90% RH
Dimensions	164mm x 83mm x 27.7 mm (6.5 in x 3.3 in x 1.1 in)
Weight	213 grams / 7.52 oz. (without battery and iOS device)
Software Support	SDK for iOS platform
Certifications	CE, FCC, RoHS, Apple MFI, IP54+



www.stimare.net

www.lineapro.store

info@stimare.net

info@lineapro.store

USA +1-720-257-7070

UK +44-208-0998071

Ireland +353-1-6854600

We are the experts in:

BARCODE SCANNING

MOBILE PRINTING

POINT-OF-SALE (POS)

*iPhone 6/6S headphone jack will be blocked using the Infinea X7